



Katalog

Silikonslanger



Rubberstyle AS - Finnestadsvingen 36 - 4029 Stavanger - tlf: 51542800 - salg@rubberstyle.com



Index

Universal High Performance Silicone hoses

Straight silicone hoses	6
Flexible silicone hoses	10
Wire reinforced silicone hoses	12
Vacuum silicone hoses	12
Silicone hose elbows	14
Straight reducing silicone hoses	22
T-Piece silicone hoses	30
Hump bellow silicone hoses	30
Silicone hoses according to SAE-J2006-R3	32
Hose clamps	36





Universal High Performance Silicone hoses

Traditional rubber hoses are increasingly being replaced by universal silicone hoses within the automotive but also in other industrial sectors. The good temperature resistance, flexibility, durability, excellent thermal and electrical insulation properties of silicone tubing, making them particularly suitable for use as coolant, radiator or turbo hoses.

This brochure provides an overview of the most common sizes. We supply these various sizes and color from stock. We also can provide you on request different sizes and color.



Automotive
Cartuning
Motorsport
Marine
Industrial engines

Straight silicone hoses 1000 mm

- temperature range : - 60° C till + 180° C
- hardness : 65 – 75 Shore A
- tensile strength : 6,0 Mpa
- reinforcement : 3-4 polyester fabric reinforcements
- tolerance wall : -0.5 till 1.0 mm
- properties : Excellent ozone and UV resistance. Resistant to electrochemical degradation.
- length : 1000 mm, on request, hoses can be cut to size.
- applications : For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
- color : blue, black, black mat, red, orange, green, light green



Straight silicone hoses
1000 mm

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96000006	6,5	1/4"	4,0	9,8	29,5	● ●
96000008	8,0	5/16"	4,0	9,8	29,5	● ●
96000009	9,5	3/8"	4,0	9,8	29,5	● ●
96000011	11	7/16"	4,0	8,0	24,0	● ●
96000013	13	1/2"	4,0	8,0	24,0	● ●
96000016	16	5/8"	4,0	8,0	24,0	● ●
96000019	19	3/4"	4,0	5,8	17,5	● ●
96000022	22	7/8"	4,0	5,8	17,5	● ●
96000025	25	1"	4,5	5,8	17,5	● ● ● ● ● ● ●
96000028	28	1 1/8"	4,5	5,8	17,5	● ●
96000030	30	1 3/16"	4,5	4,2	12,5	● ●
96000032	32	1 1/4"	4,5	4,2	12,5	● ● ● ● ● ● ●
96000035	35	1 3/8"	4,5	4,2	12,5	● ●
96000038	38	1 1/2"	4,5	3,3	10,0	● ● ● ● ● ● ●
96000040	40	1 5/8"	4,5	3,3	10,0	● ●
96000042	42	1 11/16"	4,5	3,3	10,0	● ●
96000045	45	1 3/4"	4,5	3,2	9,5	● ● ● ● ● ● ●
96000048	48	1 7/8"	4,5	3,2	9,5	● ●
96000051	51	2"	5,0	3,2	9,5	● ● ● ● ● ● ●
96000054	54	2 1/8"	5,0	3,2	9,5	● ●
96000057	57	2 1/4"	5,0	2,7	8,0	● ●
96000060	60	2 3/8"	5,0	2,7	8,0	● ●
96000063	63	2 1/2"	5,0	2,7	8,0	● ● ● ● ● ● ●
96000065	65	2 9/16"	5,0	2,7	8,0	● ●
96000068	68	2 11/16"	5,0	2,5	7,5	● ●
96000070	70	2 3/4"	5,0	2,5	7,5	● ●
96000076	76	3"	5,5	2,5	7,5	● ● ● ● ● ● ●
96000080	80	3 1/8"	5,5	2,5	7,5	● ●
96000083	83	3 1/4"	5,5	1,8	5,5	● ●
96000090	90	3 1/2"	5,5	1,8	5,5	● ●
96000102	102	4"	5,5	1,5	4,5	● ●
96000114	114	4 1/2"	5,5	1,2	3,5	● ●
96000127	127	5"	5,5	1,2	3,5	● ●
96000152	152	6"	5,5	1,2	3,5	● ●

Straight silicone hoses 100 mm

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical
degradation.	
length	: 100 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat



Straight silicone hoses 4000 mm

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical
degradation.	
length	: 4000 mm, On request, hoses can be cut to size.
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red



**Straight silicone hoses
100 mm**

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96010025	25	1"	4,5	5,8	17,5	● ● ●
96010032	32	1 1/4"	4,5	4,2	12,5	● ● ●
96010035	35	1 3/8"	4,5	4,2	12,5	● ● ●
96010038	38	1 1/2"	4,5	3,3	10,0	● ● ●
96010045	45	1 3/4"	4,5	3,2	9,5	● ● ●
96010051	51	2"	5,0	3,2	9,5	● ● ●
96010054	54	2 1/8"	5,0	3,2	9,5	● ● ●
96010057	57	2 1/4"	5,0	2,7	8,0	● ● ●
96010060	60	2 3/8"	5,0	2,7	8,0	● ● ●
96010063	63	2 1/2"	5,0	2,7	8,0	● ● ●
96010070	70	2 3/4"	5,0	2,5	7,5	● ● ●
96010076	76	3"	5,5	2,5	7,5	● ● ●
96010080	80	3 1/8"	5,5	2,5	7,5	● ● ●
96010083	83	3 1/4"	5,5	1,8	5,5	● ● ●
96010090	90	3 1/2"	5,5	1,8	5,5	● ● ●
96010102	102	4"	5,5	1,5	4,5	● ● ●
96010127	127	5"	5,5	1,2	3,5	● ● ●
96010152	152	6"	5,5	1,2	3,5	● ● ●

**Straight silicone hoses
4000 mm**

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96050009	9,5	3/8"	4,0	9,8	29,5	● ● ● ●
96050013	13	1/2"	4,0	8,0	24,0	● ● ● ●
96050016	16	5/8"	4,0	8,0	24,0	● ● ● ●
96050019	19	3/4"	4,0	5,8	17,5	● ● ● ●

Flexible silicone hoses 1000 mm

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 1000 mm, on request, hoses can be cut to size.
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red



Flexible silicone hoses
1000 mm

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96110009	9,5	3/8"	4,0	9,8	29,5	● ● ● ●
96110011	11	7/16"	4,0	8,0	24,0	● ● ● ●
96110013	13	1/2"	4,0	8,0	24,0	● ● ● ●
96110016	16	5/8"	4,0	8,0	24,0	● ● ● ●
96110019	19	3/4"	4,0	5,8	17,5	● ● ● ●
96110022	22	7/8"	4,0	5,8	17,5	● ● ● ●
96110025	25	1"	4,5	5,8	17,5	● ● ● ●
96110028	28	1 1/8"	4,5	5,8	17,5	● ● ● ●
96110030	30	1 3/16"	4,5	4,2	12,5	● ● ● ●
96110032	32	1 1/4"	4,5	4,2	12,5	● ● ● ●
96110035	35	1 3/8"	4,5	4,2	12,5	● ● ● ●
96110038	38	1 1/2"	4,5	3,3	10,0	● ● ● ●
96110040	40	1 5/8"	4,5	3,3	10,0	● ● ● ●
96110045	45	1 3/4"	4,5	3,2	9,5	● ● ● ●
96110048	48	1 7/8"	4,5	3,2	9,5	● ● ● ●
96110051	51	2"	5,0	3,2	9,5	● ● ● ●

Wire reinforced silicone hoses 1000 mm

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 1000 mm, on request, hoses can be cut to size.
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Vacuum silicone hoses

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 1000 mm, on request, hoses can be cut to size.
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black



Wire reinforced silicone hoses
1000 mm

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96210009	9,5	3/8"	4,0	9,8	29,5	● ●
96210011	11	7/16"	4,0	8,0	24,0	● ●
96210013	13	1/2"	4,0	8,0	24,0	● ●
96210016	16	5/8"	4,0	8,0	24,0	● ●
96210019	19	3/4"	4,0	5,8	17,5	● ●
96210022	22	7/8"	4,0	5,8	17,5	● ●
96210025	25	1"	4,5	5,8	17,5	● ● ● ● ● ● ●
96210028	28	1 1/8"	4,5	5,8	17,5	● ●
96210030	30	1 3/16"	4,5	4,2	12,5	● ●
96210032	32	1 1/4"	4,5	4,2	12,5	● ● ● ● ● ● ●
96210035	35	1 3/8"	4,5	4,2	12,5	● ●
96210038	38	1 1/2"	4,5	3,3	10,0	● ● ● ● ● ● ●
96210040	40	1 5/8"	4,5	3,3	10,0	● ●
96210045	45	1 3/4"	4,5	3,2	9,5	● ● ● ● ● ● ●
96210048	48	1 7/8"	4,5	3,2	9,5	● ●
96210051	51	2"	5,0	3,2	9,5	● ● ● ● ● ● ●

Vacuum silicone hoses

code	Ø innersize (mm)	wall thickness (mm)	color
96080003	3	2	● ●
96080004	4	2	● ●
96080005	5	2	● ●
96080006	6	2,5	● ●
96080007	7	2,5	● ●
96080008	8	3	● ●
96080009	9	3	● ●

Silicone hose elbows 45°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 150 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Silicone hose elbows 45°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96310006	6,5	1/4"	4,0	9,8	29,5	● ● ●
96310008	8,0	5/16"	4,0	9,8	29,5	● ● ●
96310009	9,5	3/8"	4,0	9,8	29,5	● ● ●
96310011	11	7/16"	4,0	8,0	24,0	● ● ●
96310013	13	1/2"	4,0	8,0	24,0	● ● ●
96310016	16	5/8"	4,0	8,0	24,0	● ● ●
96310019	19	3/4"	4,0	5,8	17,5	● ● ●
96310022	22	7/8"	4,0	5,8	17,5	● ● ●
96310025	25	1"	4,5	5,8	17,5	● ● ● ● ● ● ●
96310028	28	1 1/8"	4,5	5,8	17,5	● ● ●
96310030	30	1 3/16"	4,5	4,2	12,5	● ● ●
96310032	32	1 1/4"	4,5	4,2	12,5	● ● ● ● ● ● ●
96310035	35	1 3/8"	4,5	4,2	12,5	● ● ●
96310038	38	1 1/2"	4,5	3,3	10,0	● ● ● ● ● ● ●
96310040	40	1 5/8"	4,5	3,3	10,0	● ● ●
96310045	45	1 3/4"	4,5	3,2	9,5	● ● ● ● ● ● ●
96310048	48	1 7/8"	4,5	3,2	9,5	● ● ●
96310051	51	2"	5,0	3,2	9,5	● ● ● ● ● ● ●
96310054	54	2 1/8"	5,0	3,2	9,5	● ● ●
96310057	57	2 1/4"	5,0	2,7	8,0	● ● ●
96310060	60	2 3/8"	5,0	2,7	8,0	● ● ●
96310063	63	2 1/2"	5,0	2,7	8,0	● ● ● ● ● ● ●
96310065	65	2 9/16"	5,0	2,7	8,0	● ● ●
96310068	68	2 11/16"	5,0	2,5	7,5	● ● ●
96310070	70	2 3/4"	5,0	2,5	7,5	● ● ●
96310076	76	3"	5,5	2,5	7,5	● ● ● ● ● ● ●
96310080	80	3 1/8"	5,5	2,5	7,5	● ● ●
96310083	83	3 1/4"	5,5	1,8	5,5	● ● ●
96310090	90	3 1/2"	5,5	1,8	5,5	● ● ●
96310102	102	4"	5,5	1,5	4,5	● ● ●
96310114	114	4 1/2"	5,5	1,2	3,5	● ● ●

Silicone hose elbows 90°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 150 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Silicone hose elbows 90°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96320006	6,5	1/4"	4,0	9,8	29,5	● ● ●
96320008	8,0	5/16"	4,0	9,8	29,5	● ● ●
96320009	9,5	3/8"	4,0	9,8	29,5	● ● ●
96320011	11	7/16"	4,0	8,0	24,0	● ● ●
96320013	13	1/2"	4,0	8,0	24,0	● ● ●
96320016	16	5/8"	4,0	8,0	24,0	● ● ●
96320019	19	3/4"	4,0	5,8	17,5	● ● ●
96320022	22	7/8"	4,0	5,8	17,5	● ● ●
96320025	25	1"	4,5	5,8	17,5	● ● ● ● ● ● ●
96320028	28	1 1/8"	4,5	5,8	17,5	● ● ●
96320030	30	1 3/16"	4,5	4,2	12,5	● ● ●
96320032	32	1 1/4"	4,5	4,2	12,5	● ● ● ● ● ● ●
96320035	35	1 3/8"	4,5	4,2	12,5	● ● ●
96320038	38	1 1/2"	4,5	3,3	10,0	● ● ● ● ● ● ●
96320041	41	1 5/8"	4,5	3,3	10,0	● ● ●
96320045	45	1 3/4"	4,5	3,2	9,5	● ● ● ● ● ● ●
96320048	48	1 7/8"	4,5	3,2	9,5	● ● ●
96320051	51	2"	5,0	3,2	9,5	● ● ● ● ● ● ●
96320054	54	2 1/8"	5,0	3,2	9,5	● ● ●
96320057	57	2 1/4"	5,0	2,7	8,0	● ● ●
96320060	60	2 3/8"	5,0	2,7	8,0	● ● ●
96320063	63	2 1/2"	5,0	2,7	8,0	● ● ● ● ● ● ●
96320065	65	2 9/16"	5,0	2,7	8,0	● ● ●
96320068	68	2 11/16"	5,0	2,5	7,5	● ● ●
96320070	70	2 3/4"	5,0	2,5	7,5	● ● ●
96320076	76	3"	5,5	2,5	7,5	● ● ● ● ● ● ●
96320080	80	3 1/8"	5,5	2,5	7,5	● ● ●
96320083	83	3 1/4"	5,5	1,8	5,5	● ● ●
96320090	90	3 1/2"	5,5	1,8	5,5	● ● ●
96320102	102	4"	5,5	1,5	4,5	● ● ●
96320114	114	4 1/2"	5,5	1,2	3,5	● ● ●

Silicone hose elbows 135°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 100 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat



Silicone hose elbows 135°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96330006	6,5	1/4"	4,0	9,8	29,5	● ● ●
96330008	8,0	5/16"	4,0	9,8	29,5	● ● ●
96330009	9,5	3/8"	4,0	9,8	29,5	● ● ●
96330011	11	7/16"	4,0	8,0	24,0	● ● ●
96330013	13	1/2"	4,0	8,0	24,0	● ● ●
96330016	16	5/8"	4,0	8,0	24,0	● ● ●
96330019	19	3/4"	4,0	5,8	17,5	● ● ●
96330022	22	7/8"	4,0	5,8	17,5	● ● ●
96330025	25	1"	4,5	5,8	17,5	● ● ●
96330028	28	1 1/8"	4,5	5,8	17,5	● ● ●
96330030	30	1 3/16"	4,5	4,2	12,5	● ● ●
96330032	32	1 1/4"	4,5	4,2	12,5	● ● ●
96330035	35	1 3/8"	4,5	4,2	12,5	● ● ●
96330038	38	1 1/2"	4,5	3,3	10,0	● ● ●
96330041	41	1 5/8"	4,5	3,3	10,0	● ● ●
96330045	45	1 3/4"	4,5	3,2	9,5	● ● ●
96330048	48	1 7/8"	4,5	3,2	9,5	● ● ●
96330051	51	2"	5,0	3,2	9,5	● ● ●
96330054	54	2 1/8"	5,0	3,2	9,5	● ● ●
96330057	57	2 1/4"	5,0	2,7	8,0	● ● ●
96330060	60	2 3/8"	5,0	2,7	8,0	● ● ●
96330063	63	2 1/2"	5,0	2,7	8,0	● ● ●
96330065	65	2 9/16"	5,0	2,7	8,0	● ● ●
96330068	68	2 11/16"	5,0	2,5	7,5	● ● ●
96330070	70	2 3/4"	5,0	2,5	7,5	● ● ●
96330076	76	3"	5,5	2,5	7,5	● ● ●
96330080	80	3 1/8"	5,5	2,5	7,5	● ● ●
96330083	83	3 1/4"	5,5	1,8	5,5	● ● ●
96330090	90	3 1/2"	5,5	1,8	5,5	● ● ●
96330102	102	4"	5,5	1,5	4,5	● ● ●

Silicone hose elbows 180°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 100 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat



Silicone hose elbows 180°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96340006	6,5	1/4"	4,0	9,8	29,5	● ● ●
96340008	8,0	5/16"	4,0	9,8	29,5	● ● ●
96340009	9,5	3/8"	4,0	9,8	29,5	● ● ●
96340011	11	7/16"	4,0	8,0	24,0	● ● ●
96340013	13	1/2"	4,0	8,0	24,0	● ● ●
96340016	16	5/8"	4,0	8,0	24,0	● ● ●
96340019	19	3/4"	4,0	5,8	17,5	● ● ●
96340022	22	7/8"	4,0	5,8	17,5	● ● ●
96340025	25	1"	4,5	5,8	17,5	● ● ●
96340028	28	1 1/8"	4,5	5,8	17,5	● ● ●
96340030	30	1 3/16"	4,5	4,2	12,5	● ● ●
96340032	32	1 1/4"	4,5	4,2	12,5	● ● ●
96340035	35	1 3/8"	4,5	4,2	12,5	● ● ●
96340038	38	1 1/2"	4,5	3,3	10,0	● ● ●
96340041	41	1 5/8"	4,5	3,3	10,0	● ● ●
96340045	45	1 3/4"	4,5	3,2	9,5	● ● ●
96340048	48	1 7/8"	4,5	3,2	9,5	● ● ●
96340051	51	2"	5,0	3,2	9,5	● ● ●
96340054	54	2 1/8"	5,0	3,2	9,5	● ● ●
96340057	57	2 1/4"	5,0	2,7	8,0	● ● ●
96340060	60	2 3/8"	5,0	2,7	8,0	● ● ●
96340063	63	2 1/2"	5,0	2,7	8,0	● ● ●
96340065	65	2 9/16"	5,0	2,7	8,0	● ● ●
96340068	68	2 11/16"	5,0	2,5	7,5	● ● ●
96340070	70	2 3/4"	5,0	2,5	7,5	● ● ●
96340076	76	3"	5,5	2,5	7,5	● ● ●
96340080	80	3 1/8"	5,5	2,5	7,5	● ● ●
96340083	83	3 1/4"	5,5	1,8	5,5	● ● ●
96340090	90	3 1/2"	5,5	1,8	5,5	● ● ●
96340102	102	4"	5,5	1,5	4,5	● ● ●

Straight reducing silicone hoses

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 127 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Straight reducing silicone hoses

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
9640016013	16 > 13	5/8" > 1/2"	4,0	8,0	24,0	● ●
9640019013	19 > 13	3/4" > 1/2"	4,0	5,8	17,5	● ●
9640019016	19 > 16	3/4" > 5/8"	4,0	5,8	17,5	● ●
9640022016	22 > 16	7/8" > 5/8"	4,0	5,8	17,5	● ●
9640022019	22 > 19	7/8" > 3/4"	4,0	5,8	17,5	● ●
9640025016	25 > 16	1" > 5/8"	4,5	5,8	17,5	● ●
9640025019	25 > 19	1" > 3/4"	4,5	5,8	17,5	● ●
9640028022	28 > 22	1 1/8" > 7/8"	4,5	5,8	17,5	● ●
9640028025	28 > 25	1 1/8" > 1"	4,5	5,8	17,5	● ●
9640032025	32 > 25	1 1/4" > 1"	4,5	4,2	12,5	● ●
9640032028	32 > 28	1 1/4" > 1 1/8"	4,5	4,2	12,5	● ●
9640035025	35 > 25	1 3/8" > 1"	4,5	4,2	12,5	● ●
9640035028	35 > 28	1 3/8" > 1 1/8"	4,5	4,2	12,5	● ●
9640035032	35 > 32	1 3/8" > 1 1/4"	4,5	4,2	12,5	● ●
9640038022	38 > 22	1 1/2" > 7/8"	4,5	3,3	10,0	● ●
9640038025	38 > 25	1 1/2" > 1"	4,5	3,3	10,0	● ● ● ● ● ● ●
9640038028	38 > 28	1 1/2" > 1 1/8"	4,5	3,3	10,0	● ● ● ● ● ● ●
9640038032	38 > 32	1 1/2" > 1 1/4"	4,5	3,3	10,0	● ● ● ● ● ● ●
9640038035	38 > 35	1 1/2" > 1 3/8"	4,5	3,3	10,0	● ● ● ● ● ● ●
9640040035	40 > 35	1 5/8" > 1 3/8"	4,5	3,3	10,0	● ● ● ● ● ● ●
9640045032	45 > 32	1 3/4" > 1 1/4"	4,5	3,2	9,5	● ● ● ● ● ● ●
9640045038	45 > 38	1 3/4" > 1 1/2"	4,5	3,2	9,5	● ● ● ● ● ● ●
9640051038	51 > 38	2" > 1 1/2"	5,0	3,2	9,5	● ● ● ● ● ● ●
9640051045	51 > 45	2" > 1 3/4"	5,0	3,2	9,5	● ● ● ● ● ● ●
9640054051	54 > 51	2 1/8" > 2"	5,0	3,2	9,5	● ●
9640057051	57 > 51	2 1/4" > 2"	5,0	2,7	8,0	● ●
9640057038	57 > 38	2 1/4" > 1 1/2"	5,0	2,7	8,0	● ●
9640057045	57 > 45	2 1/4" > 1 3/4"	5,0	2,7	8,0	● ●
9640060050	60 > 50	2 3/8" > 2"	5,0	2,7	8,0	● ● ● ● ● ● ●
9640063051	63 > 51	2 1/2" > 2"	5,0	2,7	8,0	● ●
9640063038	63 > 38	2 1/2" > 1 1/2"	5,0	2,7	8,0	● ●
9640063045	63 > 45	2 1/2" > 1 3/4"	5,0	2,7	8,0	● ●
9640063057	63 > 57	2 1/2" > 2 1/4"	5,0	2,7	8,0	● ●
9640070045	70 > 45	2 3/4" > 1 3/4"	5,0	2,5	7,5	● ●
9640070050	70 > 50	2 3/4" > 2"	5,0	2,5	7,5	● ● ● ● ● ● ●
9640070057	70 > 57	2 3/4" > 2 1/4"	5,0	2,5	7,5	● ●
9640070060	70 > 60	2 3/4" > 2 3/8"	5,0	2,5	7,5	● ● ● ● ● ● ●
9640070063	70 > 63	2 3/4" > 2 1/2"	5,0	2,5	7,5	● ●

Straight reducing silicone hoses

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 127 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Straight reducing silicone hoses

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
9640076051	76 > 51	3" > 2"	5,5	2,5	7,5	● ●
9640076057	76 > 57	3" > 2 1/4"	5,5	2,5	7,5	● ●
9640076060	76 > 60	3" > 2 3/8"	5,5	2,5	7,5	● ●
9640076063	76 > 63	3" > 2 1/2"	5,5	2,5	7,5	● ● ● ● ● ● ●
9640076067	76 > 67	3" > 2 5/8"	5,5	2,5	7,5	● ●
9640076070	76 > 70	3" > 2 3/4"	5,5	2,5	7,5	● ●
9640080070	80 > 70	3 1/8" > 2 3/4"	5,5	2,5	7,5	● ●
9640083057	83 > 57	3 1/4" > 2 1/4"	5,5	1,8	5,5	● ●
9640083063	83 > 63	3 1/4" > 2 1/2"	5,5	1,8	5,5	● ●
9640083070	83 > 70	3 1/4" > 2 3/4"	5,5	1,8	5,5	● ●
9640083076	83 > 76	3 1/4" > 3"	5,5	1,8	5,5	● ●
9640083057	89 > 57	3 3/8" > 2 1/4"	5,5	1,8	5,5	● ●
9640089063	89 > 63	3 3/8" > 2 1/2"	5,5	1,8	5,5	● ●
9640089070	89 > 70	3 3/8" > 2 3/4"	5,5	1,8	5,5	● ● ● ● ● ● ●
9640089083	89 > 83	3 3/8" > 3 1/4"	5,5	1,8	5,5	● ●
9640090076	90 > 76	3 1/2" > 3"	5,5	1,8	5,5	● ● ● ● ● ● ●
9640090080	90 > 80	3 1/2" > 3 1/8"	5,5	1,8	5,5	● ● ● ● ● ● ●
9640095070	95 > 70	3 3/4" > 2 3/4"	5,5	1,8	5,5	● ●
9640095076	95 > 76	3 3/4" > 3"	5,5	1,8	5,5	● ●
9640095083	95 > 83	3 3/4" > 3 1/4"	5,5	1,8	5,5	● ●
9640095089	95 > 89	3 3/4" > 3 3/8"	5,5	1,8	5,5	● ●
9640102063	102 > 63	4" > 2 1/2"	5,5	1,5	4,5	● ●
9640102083	102 > 83	4" > 3 1/4"	5,5	1,5	4,5	● ●
9640102089	102 > 89	4" > 3 3/8"	5,5	1,5	4,5	● ● ● ● ● ● ●
9640102095	102 > 95	4" > 3 3/4"	5,5	1,5	4,5	● ●
9640102076	102 > 76	4" > 3"	5,5	1,5	4,5	● ●
9640114089	114 > 89	4 1/2" > 3 3/8"	5,5	1,2	3,5	● ●
9640114102	114 > 102	4 1/2" > 4"	5,5	1,2	3,5	● ●
9640127102	127 > 102	5" > 4"	5,5	1,2	3,5	● ●
9640127114	127 > 114	5" > 4 1/2"	5,5	1,2	3,5	● ●

Reducing silicone hoses - elbows 45°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 150 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat



Reducing silicone hoses - elbows 45°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
9651025016	25 > 16	1" > 5/8"	4,5	5,8	17,5	● ● ●
9651025019	25 > 19	1" > 3/4"	4,5	5,8	17,5	● ● ●
9651032025	32 > 25	1 1/4" > 1"	4,5	4,2	12,5	● ● ●
9651035025	35 > 25	1 3/8" > 1"	4,5	4,2	12,5	● ● ●
9651035032	35 > 32	1 3/8" > 1 1/4"	4,5	4,2	12,5	● ● ●
9651038025	38 > 25	1 1/2" > 1"	4,5	3,3	10,0	● ● ●
9651038032	38 > 32	1 1/2" > 1 1/4"	4,5	3,3	10,0	● ● ●
9651038035	38 > 35	1 1/2" > 1 3/8"	4,5	3,3	10,0	● ● ●
9651051038	51 > 38	1 3/4" > 1 1/2"	5,0	3,2	9,5	● ● ●
9651051045	51 > 45	2" > 1 3/4"	5,0	3,2	9,5	● ● ●
9651057051	57 > 51	2 1/4" > 2"	5,0	2,7	8,0	● ● ●
9651060051	60 > 51	2 3/8" > 2"	5,0	2,7	8,0	● ● ●
9651063045	63 > 45	2 1/2" > 1 3/4"	5,0	2,7	8,0	● ● ●
9651063051	63 > 51	2 1/2" > 2"	5,0	2,7	8,0	● ● ●
9651063057	63 > 57	2 1/2" > 2 1/4"	5,0	2,7	8,0	● ● ●
9651070051	70 > 51	2 3/4" > 2"	5,0	2,5	7,5	● ● ●
9651070060	70 > 60	2 3/4" > 2 3/8"	5,0	2,5	7,5	● ● ●
9651070063	70 > 63	2 3/4" > 2 1/2"	5,0	2,5	7,5	● ● ●
9651076051	76 > 51	3" > 2"	5,5	2,5	7,5	● ● ●
9651076057	76 > 57	3" > 2 1/4"	5,5	2,5	7,5	● ● ●
9651076060	76 > 60	3" > 2 3/8"	5,5	2,5	7,5	● ● ●
9651076063	76 > 63	3" > 2 1/2"	5,5	2,5	7,5	● ● ●
9651076067	76 > 67	3" > 2 5/8"	5,5	2,5	7,5	● ● ●
9651076070	76 > 70	3" > 2 3/4"	5,5	2,5	7,5	● ● ●
9651080070	80 > 70	3 1/8" > 2 3/4"	5,5	2,5	7,5	● ● ●
9651083063	83 > 63	3 1/4" > 2 1/2"	5,5	1,8	5,5	● ● ●
9651089063	89 > 63	3 3/8" > 2 1/2"	5,5	1,8	5,5	● ● ●
9651090076	89 > 76	3 3/8" > 3"	5,5	1,8	5,5	● ● ●
9651090080	90 > 76	3 1/2" > 3"	5,5	1,8	5,5	● ● ●
9651090080	90 > 80	3 1/2" > 3 1/8"	5,5	1,8	5,5	● ● ●
9651102076	102 > 76	4" > 3"	5,5	1,8	5,5	● ● ●
9651102089	102 > 89	4" > 3 3/8"	5,5	1,5	4,5	● ● ●

Reducing silicone hoses - elbows 90°

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
leg length	: 127 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red, orange, green, light green



Reducing silicone hoses - elbows 90°

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
9652025016	25 > 16	1" > 5/8"	4,5	5,8	17,5	● ● ●
9652025019	25 > 19	1" > 3/4"	4,5	5,8	17,5	● ● ●
9652032025	32 > 25	1 1/4" > 1"	4,5	4,2	12,5	● ● ●
9652035025	35 > 25	1 3/8" > 1"	4,5	4,2	12,5	● ● ●
9652035032	35 > 32	1 3/8" > 1 1/4"	4,5	4,2	12,5	● ● ●
9652038025	38 > 25	1 1/2" > 1"	4,5	3,3	10,0	● ● ●
9652038032	38 > 32	1 1/2" > 1 1/4"	4,5	3,3	10,0	● ● ●
9652038035	38 > 35	1 1/2" > 1 3/8"	4,5	3,3	10,0	● ● ●
9652051038	51 > 38	1 3/4" > 1 1/2"	5,0	3,2	9,5	● ● ● ● ● ● ●
9652051045	51 > 45	2" > 1 3/4"	5,0	3,2	9,5	● ● ●
9652057051	57 > 51	2 1/4" > 2"	5,0	2,7	8,0	● ● ●
9652060051	60 > 51	2 3/8" > 2"	5,0	2,7	8,0	● ● ● ● ● ● ●
9652063045	63 > 45	2 1/2" > 1 3/4"	5,0	2,7	8,0	● ● ●
9652063051	63 > 51	2 1/2" > 2"	5,0	2,7	8,0	● ● ●
9652063057	63 > 57	2 1/2" > 2 1/4"	5,0	2,7	8,0	● ● ●
9652070051	70 > 51	1 3/4" > 2"	5,0	2,5	7,5	● ● ●
9652070060	70 > 60	1 3/4" > 2 3/8"	5,0	2,5	7,5	● ● ● ● ● ● ●
9652070063	70 > 63	2 3/4" > 2 1/2"	5,0	2,5	7,5	● ● ●
9652076051	76 > 51	3" > 2"	5,5	2,5	7,5	● ● ●
9652076057	76 > 57	3" > 2 1/4"	5,5	2,5	7,5	● ● ●
9652076060	76 > 60	3" > 2 3/8"	5,5	2,5	7,5	● ● ●
9652076063	76 > 63	3" > 2 1/2"	5,5	2,5	7,5	● ● ●
9652076067	76 > 67	3" > 2 5/8"	5,5	2,5	7,5	● ● ●
9652076070	76 > 70	3" > 1 3/4"	5,5	2,5	7,5	● ● ●
9652080070	80 > 70	3 1/8" > 2 3/4"	5,5	2,5	7,5	● ● ●
9652083063	83 > 63	3 1/4" > 2 1/2"	5,5	1,8	5,5	● ● ●
9652089063	89 > 63	3 3/8" > 2 1/2"	5,5	1,8	5,5	● ● ●
9652090076	90 > 76	3 1/2" > 3"	5,5	1,8	5,5	● ● ●
9652090080	90 > 80	3 1/2" > 3 1/8"	5,5	1,8	5,5	● ● ●
9652102076	102 > 76	4" > 3"	5,5	1,5	4,5	● ● ●
9652102089	102 > 89	4" > 3 3/8"	5,5	1,5	4,5	● ● ●

T-Piece silicone hoses

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 102 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red



Hump bellow silicone hoses

temperature range	: - 60° C till + 180° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 102 mm
applications	: For pressurized air or water conduction at high temperatures, can be used in vehicles and in the industrial sector.
color	: blue, black, black mat, red



T-Piece silicone hoses

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96500025	25	1"	4,5	5,8	17,5	● ● ● ●
96500032	32	1 1/4"	4,5	4,2	12,5	● ● ● ●
96500038	38	1 1/2"	4,5	3,3	10,0	● ● ● ●
96500045	45	1 5/8"	4,5	3,2	9,5	● ● ● ●
96500051	51	2"	5,0	3,2	9,5	● ● ● ●
96500054	54	2 1/8"	5,0	3,2	9,5	● ● ● ●
96500060	60	2 3/8"	5,0	2,7	8,0	● ● ● ●
96500063	63	2 1/2"	5,0	2,7	8,0	● ● ● ●
96500070	70	2 3/4"	5,0	2,5	7,5	● ● ● ●
96500076	76	3"	5,5	2,5	7,5	● ● ● ●

Hump bellow silicone hoses

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96610025	25	1"	4,5	5,8	17,5	● ● ● ●
96610032	32	1 1/4"	4,5	4,2	12,5	● ● ● ●
96610038	38	1 1/2"	4,5	3,3	10,0	● ● ● ●
96610045	45	1 5/8"	4,5	3,2	9,5	● ● ● ●
96610051	51	2"	5,0	3,2	9,5	● ● ● ●
96610057	57	2 1/4"	5,0	2,7	8,0	● ● ● ●
96610060	60	2 3/8"	5,0	2,7	8,0	● ● ● ●
96610063	63	2 1/2"	5,0	2,7	8,0	● ● ● ●
96610070	70	2 3/4"	5,0	2,5	7,5	● ● ● ●
96610076	76	3"	5,5	2,5	7,5	● ● ● ●
96610080	80	3 1/8"	5,5	2,5	7,5	● ● ● ●
96610083	83	3 1/4"	5,5	1,8	5,5	● ● ● ●
96610090	90	3 1/2"	5,5	1,8	5,5	● ● ● ●
96610102	102	4"	5,5	1,5	4,5	● ● ● ●
96610114	114	4 1/2"	5,5	1,2	3,5	● ● ● ●

Silicone hoses according to SAE-J2006-R3

temperature range	: - 60° C tot + 210° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
length	: 1000 mm
applications	: The hoses are approved as exhaust gas hoses for combustion engines on yachts. The exhaust gas shall be water cooled. Meets operating requirements of ISO/DIS 13363 and SAE J2006 (Style R3 marine exhaust gas hoses).
color	: blue



Silicone hoses according to SAE-J2006-R3

code	Ø innersize (mm)	Ø innersize (inch)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96020042	42	1 11/16"	4,5	3,3	10,0	●
96020045	45	1 5/8"	4,5	3,2	9,5	●
96020051	51	2"	5,0	3,2	9,5	●
96020060	60	2 3/8"	5,0	2,7	8,0	●
96020070	70	2 3/4"	5,0	2,5	7,5	●
96020076	76	3"	5,5	2,5	7,5	●
96020102	102	4"	5,5	1,5	4,5	●
96020127	127	5"	5,5	1,2	3,5	●
96020152	152	6"	5,5	1,2	3,5	●
96020203	203	8"	5,5	1,2	3,5	●

Hump bellow silicone hoses according to SAE-J2006-R3

temperature range	: - 60° C tot + 210° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
applications	: The hoses are approved as exhaust gas hoses for combustion engines on yachts. The exhaust gas shall be water cooled. Meets operating requirements of ISO/DIS 13363 and SAE J2006 (Style R3 marine exhaust gas hoses).
color	: blue



Hump bellow silicone hoses double according to SAE-J2006-R3

temperature range	: - 60° C tot + 210° C
hardness	: 65 – 75 Shore A
tensile strength	: 6,0 Mpa
reinforcement	: 3-4 polyester fabric reinforcements
tolerance wall	: -0.5 till 1.0 mm
properties	: Excellent ozone and UV resistance. Resistant to electrochemical degradation.
applications	: The hoses are approved as exhaust gas hoses for combustion engines on yachts. The exhaust gas shall be water cooled. Meets operating requirements of ISO/DIS 13363 and SAE J2006 (Style R3 marine exhaust gas hoses).
color	: blue



Hump bellow silicone hoses according to SAE-J2006-R3

code	Ø innersize (mm)	Ø innersize (inch)	hight (mm)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96620051	51	2"	152	5,0	3,2	9,5	●
96620063	63	2 1/2"	152	5,0	2,7	8,0	●
96620076	76	3"	152	5,5	2,5	7,5	●
96620089	89	3 3/8"	152	5,5	1,8	5,5	●
96620102	102	4"	152	5,5	1,5	4,5	●
96620127	127	5"	152	5,5	1,2	3,5	●
96620152	152	6"	203	5,5	1,2	3,5	●
96620203	203	8"	305	5,5	1,2	3,5	●

Hump bellow silicone hoses double according to SAE-J2006-R3

code	Ø innersize (mm)	Ø innersize (inch)	hight (mm)	wall thickness (mm)	work pressure (kg/cm ²)	burst pressure (kg/cm ²)	color
96630051	51	2"	152	5,0	3,2	9,5	●
96630063	63	2 1/2"	202	5,0	2,7	8,0	●
96630076	76	3"	202	5,5	2,5	7,5	●
96630089	89	3 3/8"	254	5,5	1,8	5,5	●
96630102	102	4"	305	5,5	1,5	4,5	●
96630127	127	5"	305	5,5	1,2	3,5	●
96630152	152	6"	355	5,5	1,2	3,5	●
96630203	203	8"	355	5,5	1,2	3,5	●
96630254	254	10"	355	5,5	1,2	3,5	●